



**Quiet-Flow System Dimensions - TRIPLEX  
10" Manifold  
Maximum 1400 GPM**

Pump Model	Motor HP	Header Size	Isolation Valves		Motor Dia.	A	B	C	D
			IN	OUT					
385S75-1	7.5	10	8	4	6	48	30	42	92.75
385S100-2BA	10	10	8	4	6	48	30	42	99.05
385S150-2	15	10	8	4	6	48	30	42	101.65
385S200-3A	20	10	8	4	6	48	30	42	109.25
385S250-3	25	10	8	4	6	52	30	42	111.75
385S250-4B	25	10	8	4	6	52	30	42	116.85
385S300-4	30	10	8	4	6	52	30	42	119.45
385S300-5BB	30	10	8	4	6	52	30	42	124.45
385S400-5	40	10	8	4	6	52	30	42	129.55
385S400-6B	40	10	8	4	6	52	30	42	134.65
385S400-6B (8")	40	10	8	4	8	52	30	42	130.25
385S500-6	50	10	8	4	6	52	30	42	149.15
385S500-6 (8")	50	10	8	4	8	52	30	42	133.25
385S500-7A	50	10	8	4	6	52	30	42	154.75
385S500-7A (8")	50	10	8	4	8	52	30	42	138.85
385S600-7	60	10	8	4	6	52	30	42	160.75
385S600-7 (8")	60	10	8	4	8	52	30	42	141.85
385S600-8	60	10	8	4	6	52	30	42	165.75
385S600-8(8")	60	10	8	4	8	52	30	42	146.85
385S750-10	75	10	8	4	8	52	30	42	161.95
385S750-9	75	10	8	4	8	52	30	42	156.95
385S1000-11	100	10	8	4	8	52	30	42	167.05
385S1000-12	100	10	8	4	8	52	30	42	179.55
385S1000-13	100	10	8	4	8	52	30	42	184.55
475S75-1A	7.5	10	8	6	6	48	30	42	92.75
475S100-1	10	10	8	6	6	48	30	42	93.95
475S150-2B	15	10	8	6	6	48	30	42	101.65
475S200-2	20	10	8	6	6	48	30	42	104.25
475S250-3A	25	10	8	6	6	52	30	42	111.75
475S300-3	30	10	8	6	6	52	30	42	114.35
475S300-4AB	30	10	8	6	6	52	30	42	119.45
475S400-4	40	10	8	6	6	52	30	42	124.55
475S400-4 (8")	40	10	8	6	8	52	30	42	120.15
475S400-5B	40	10	8	6	6	52	30	42	129.55
475S400-5B (8")	40	10	8	6	8	52	30	42	125.15
475S500-5	50	10	8	6	6	52	30	42	144.05
475S500-5 (8")	50	10	8	6	8	52	30	42	128.15
475S500-6A	50	10	8	6	6	52	30	42	149.65
475S500-6A (8")	50	10	8	6	8	52	30	42	133.75
475S600-6	60	10	8	6	6	52	30	42	155.65
475S600-6 (8")	60	10	8	6	8	52	30	42	136.75
475S600-7	60	10	8	6	6	52	30	42	160.75
475S600-7(8")	60	10	8	6	8	52	30	42	141.85
475S750-8	75	10	8	6	8	52	30	42	151.85
475S1000-10	100	10	8	6	8	52	30	42	169.45
475S1000-11	100	10	8	6	8	52	30	42	174.55
475S1000-9	100	10	8	6	8	52	30	42	164.35
475S1250-12	125	10	8	6	8	52	30	42	179.55
475S1250-13	125	10	8	6	8	52	30	42	198.55
625S150-1A	15	10	8	6	6	48	30	42	97.85
625S250-1	25	10	8	6	6	52	30	42	102.95
625S300-2AA	30	10	8	6	6	52	30	42	111.75
625S400-2	40	10	8	6	6	52	30	42	116.85
625S400-2 (8")	40	10	8	6	8	52	30	42	112.45



**Quiet-Flow System Dimensions - TRIPLEX  
10" Manifold  
Maximum 1400 GPM**

Pump Model	Motor HP	Header Size	Isolation Valves		Motor Dia.	A	B	C	D
			IN	OUT					
625S400-2A	40	10	8	6	6	52	30	42	116.85
625S500-3AA	50	10	8	6	6	52	30	42	137.45
625S500-3AA (8")	50	10	8	6	8	52	30	42	121.55
625S600-3	60	10	8	6	6	52	30	42	143.45
625S600-3	60	10	8	6	8	52	30	42	124.55
625S600-3A	60	10	8	6	6	52	30	42	143.45
625S600-3A (8")	60	10	8	6	8	52	30	42	124.55
625S750-4A	75	10	8	6	8	52	30	42	135.65
625S750-4AA	75	10	8	6	8	52	30	42	135.65
625S1000-4	100	10	8	6	8	52	30	42	143.15
625S1000-5	100	10	8	6	8	52	30	42	149.25
625S1000-5A	100	10	8	6	8	52	30	42	149.25
625S1000-5AA	100	10	8	6	8	52	30	42	149.25
625S1250-6	125	10	8	6	8	52	30	42	169.25
625S1250-6A	125	10	8	6	8	52	30	42	169.25
625S1250-6AA	125	10	8	6	8	52	30	42	169.25
625S1250-7AA	125	10	8	6	8	52	30	42	175.45
625S1500-7	150	10	8	6	8	52	30	42	184.45
625S1500-7A	150	10	8	6	8	52	30	42	175.45
800S200-1A	20	10	8	6	6	48	30	42	100.45
800S300-1	30	10	8	6	6	52	30	42	105.55
800S400-2AA	40	10	8	6	6	52	30	42	116.85
800S400-2AA	40	10	8	6	8	52	30	42	112.45
800S500-2	50	10	8	6	6	52	30	42	131.35
800S500-2 (8")	50	10	8	6	8	52	30	42	115.45
800S500-2A	50	10	8	6	6	52	30	42	131.35
800S500-2A (8")	50	10	8	6	8	52	30	42	115.45
800S600-3AA	60	10	8	6	6	52	30	42	143.45
800S600-3AA (8")	60	10	8	6	8	52	30	42	124.55
800S750-3	75	10	8	6	8	52	30	42	129.55
800S750-3A	75	10	8	6	8	52	30	42	129.55
800S1000-4	100	10	8	6	8	52	30	42	143.15
800S1000-4A	100	10	8	6	8	52	30	42	143.15
800S1000-4AA	100	10	8	6	8	52	30	42	143.15
800S1250-5	125	10	8	6	8	52	30	42	163.15
800S1250-5A	125	10	8	6	8	52	30	42	163.15
800S1250-5AA	125	10	8	6	8	52	30	42	163.15
1100S300-1A	30	10	8	6	6	52	30	42	111.05
1100S400-1	40	10	8	6	6	52	30	42	116.15
1100S400-1 (8 ")	40	10	8	6	8	52	30	42	111.75
1100S600-2AA	60	10	8	6	6	52	30	42	143.65
1100S600-2AA (8")	60	10	8	6	8	52	30	42	124.75
1100S750-2A	75	10	8	6	8	52	30	42	129.75
1100S1000-2	100	10	8	6	8	52	30	42	137.25
1100S1000-3AA	100	10	8	6	8	52	30	42	144.25
1100S1250-3	125	10	8	6	8	52	30	42	158.15
1100S1250-3A	125	10	8	6	8	52	30	42	158.15
1100S1500-4A	150	10	8	6	8	52	30	42	174.05
1100S1500-4AA	150	10	8	6	8	52	30	42	174.05
1100S1750-4	175	10	8	6	8	52	30	42	174.05
1100S1750-5AA	175	10	8	6	8	52	30	42	188.95
1100S1750-5AA (10")	175	10	8	6	10	52	30	42	173.13
1100S2000-5	200	10	8	6	8	52	30	42	197.95
1100S2000-5 (10")	200	10	8	6	10	52	30	42	173.13



**Quiet-Flow System Dimensions - TRIPLEX  
10" Manifold  
Maximum 1400 GPM**

Pump Model	Motor HP	Header Size	Isolation Valves		Motor Dia.	A	B	C	D
			IN	OUT					
1100S2000-5A	200	10	8	6	8	52	30	42	188.95
1100S2000-5A (10")	200	10	8	6	10	52	30	42	168.89
1100S2500-61	250	10	8	6	10	52	30	42	189.68
1100S2500-6A1	250	10	8	6	10	52	30	42	189.68
1100S2500-6AA1	250	10	8	6	10	52	30	42	180.13

Notes:

1. All dimensions are in inches unless specified otherwise.
2. Not for construction purposes unless certified.
3. Structural members are 2" Stainless Steel tubing unless indicated otherwise.
4. See Drawing #DVQF-VFD-LL for references to measurements